


## PVDF Paint System

26 Gauge



Linen White (81)



Khaki (88)



Burnished Slate (49)



Classic Green (66)



Ocean Blue (35)




Zinc Grey (29)



Patriot Red (73)



Copper Penny (W92)




Metallic Silver (K7)




Matte Black (106)

## MS Colorfast45<sup>®</sup> Paint System

29\* & 26 Gauge



Polar White (80)



White (30)



Light Stone (63)



Mocha Tan (22)



Brown (12)



Patriot Red (73)



Red (24)



Burgundy (15)



Ocean Blue (35)



Hawaiian Blue (70)



Ash Grey (25)



Charcoal (17)



Patina Green (58)




Forest Green (26)



Burnished Slate (49)



Black (06)



Galvalume (41)











Non-Painted Finish 25 Year Warranty



All Colors Meet or Exceed Steep Slope  
ENERGY STAR<sup>®</sup> Requirements

*\*29 Gauge Colors shown are available in Classic Rib,  
Pro-Panel II, R-Panel and U-Panel profiles only.  
Color samples are close representations but are limited by printing  
and viewing conditions. Actual samples are available by request.*

MS(2RX) 5/19

Profile	Panel Name	Coverage	Gauge	Testing and Approvals
	Vertical Seam	12", 16", 18"	26	2010 FBC Approved (Roof): 1/2" Plywood 11560.10 Class 4 Impact Resistance: UL 2218
	Image II™	12" & 16"	26	Miami-Dade County: NOA 08-0229.12 2010 FBC Approved (Roof): 5/8" Plywood 11560.3 2010 FBC Approved (Roof): 1/2" Plywood 11560.4
	7/8" Corrugated	Roof 32" Wall 34 <sup>2</sup> / <sub>3</sub> "	26	Class 90 Wind Uplift: UL 580, Const. #649 Class A Fire Resistance: UL 790 Class 4 Impact Resistance: UL 2218
	Span-Line 36A	36"	26	2010 FBC Approved (Wall): 16 Ga. Girts 9482.6
	R-Panel/PBR-Panel	36"	26	2010 FBC Approved (Wall): 16 Ga. Girts 9482.4 2010 FBC Approved (Roof): 1/2" Plywood 14645.11 2010 FBC PBR only (Roof): 16 Ga. Purlins 10999.7
	U-Panel/PBU-Panel	36"	26	Class 90 Wind Uplift: UL 580, Const. #39 Class A Fire Resistance: UL 790 Class 4 Impact Resistance: UL 2218
	Classic Rib®	36"	26	2010 FBC Approved (Wall): 16 Ga. Girts 9482.2 2010 FBC Approved (Roof): 16 Ga. Purlins 10999.3 2010 FBC Approved (Roof): 1/2" Plywood 14645.7 2010 FBC Approved (Roof): 5/8" Plywood 15478.2
	Pro-Panel II®	36"	26	2010 FBC Approved (Roof): 1/2" Plywood 14645.12 Class A Fire Resistance: UL 790 Class 4 Impact Resistance: UL 2218
	V-Line 32	32"	26	Class 90 Wind Uplift: UL 580, Const. #187 Class A Fire Resistance: UL 790 Class 4 Impact Resistance: UL 2218
	Soffit Panel	12"	26	No Testing or Approvals for 26 Ga. panels

PVDF Color	SR	TE	SRI
Burnished Slate (49)	0.30	0.85	30
Classic Green (66)	0.32	0.86	33
Copper Penny (W92)	0.45	0.85	50
Khaki (88)	0.35	0.87	37
Linen White (81)	0.73	0.86	89
Matte Black (106)	0.25	0.83	22
Metallic Silver (K7)	0.60	0.77	68
Ocean Blue (35)	0.29	0.86	29
Patriot Red (73)	0.46	0.86	52
Zinc Grey (29)	0.41	0.86	45

MS Colorfast45®	SR	TE	SRI
Ash Grey (25)	0.37	0.88	40
Black (06)	0.20	0.86	17
Brown (12)	0.31	0.87	32
Burgundy (15)	0.25	0.87	24
Burnished Slate (49)	0.31	0.87	32
Charcoal (17)	0.30	0.87	31
Forest Green (26)	0.27	0.87	27
Galvalume (41) <i>non-painted</i>	0.67	0.14	56
Hawaiian Blue (70)	0.32	0.87	33
Light Stone (63)	0.50	0.86	58
Mocha Tan (22)	0.52	0.87	60
Ocean Blue (35)	0.30	0.88	31
Patina Green (56)	0.29	0.86	29
Patriot Red (73)	0.35	0.88	38
Polar White (80)	0.58	0.87	68
Red (24)	0.30	0.86	30
White (30)	0.57	0.88	67



7110 Stuart Avenue  
 Jacksonville, FL 32254  
 800.394.4419 Toll Free  
 904.783.3660 Phone  
 800.413.3292 Toll Free Fax  
 904.783.9175 Fax