

Wall Fastener Spacing (feet)

Wind Speed (mph) Exposure Category
120C

Gauge	Field	Edge
29 ga	-22.7 psf 2.00	-28.1 psf 2.00

130C

Gauge	Field	Edge
29 ga	-26.7 psf 2.00	-33 psf 2.00

140C

Gauge	Field	Edge
29 ga	-31 psf 2.00	-38.2 psf 2.00

150C

Gauge	Field	Edge
29 ga	-35.5 psf 2.00	-43.9 psf 2.00

160C

Gauge	Field	Edge
29 ga	-40.4 psf 2.00	-49.9 psf 2.00

170C

Gauge	Field	Edge
29 ga	-45.7 psf 2.00	-56.4 psf 2.00

180C

Gauge	Field	Edge
29 ga	-51.2 psf 2.00	-63.2 psf 2.00

190C

Gauge	Field	Edge
29 ga	-57 psf 2.00	-70.4 psf 2.00

Notes:

1. Allowable spacing is based on a Design Pressures listed in the FBC 2020 Approval, FL9482.3 and determined by linear interpolation of those values. 1/3 increase is not included for wind. The fasteners and fastening patterns are shown in the Approval.
2. Allowable spacing is based on an applied load determined using ASCE 7-10 for the Wind Speeds, Wind Exposure Categories, assuming 10 square feet " of tributary area, Enclosed building, 3 or more span case, Topographic Factor of 1, and Mean Roof Height of 25 feet.
3. Allowable spacing is determined for wind pressure and suction using the combination $0.6W$ for each.

- ④ - FIELD α - LEAST OF 10% MINIMUM BUILDING WIDTH OR 40% OF MEAN ROOF HEIGHT BUT NOT LESS THAN 3'.
- ⑤ - EDGE

